

FLESSIBILI
FLEXIBLES

DN 8




TUBI FLESSIBILI PER RUBINETTERIA - FLEXIBLE HOSES FOR FAUCETS

DATI TECNICI - TECHNICAL DATA

Tubo flessibile trecciato made in Italy in acciaio Inox AISI 304 con interno in gomma alimentare EPDM utilizzato per il collegamento tra la rete idrica e la rubinetteria sanitaria o cassette W.C.e adatto a qualsiasi altro impiego sanitario. Tutti i flessibili sono raccordati con macchine automatiche ed il risultato è l’assoluta precisione di ogni pezzo prodotto per una garanzia di totale qualità.

Made in Italy braided hose in AISI 304 stainless steel with internal in EPDM rubber, used for the connection between the water mains and the sanitary fittings or W.C. flushing tanks. All the hoses are produced with automatic machines and the result is the absolute precision of each produced piece for a total quality guarantee.

CARATTERISTICHE - FEATURES

 TEMPERATURA MASSIMA D'IMPIEGO MAX OPERATING TEMPERATURE	 TEMPERATURA D'ESERCIZIO WORKING TEMPERATURE	 PRESSIONE D'ESERCIZIO WORKING PRESSURE	 PORTATA A 3 BAR FLOW RATE AT 3 BAR	 DIAMETRO Ø DIAMETER Ø	 FORO MINIMO PASSAGGIO D'ACQUA FITTING INNER DIAMETER	 RAGGIO CURVATURA MINIMO MINIMUM BENDING RADIUS
+70°C	-5°C - +90°C	10 BAR	29 lit/min	INTERNO INNER 8 mm ESTERNO OUTER 12 mm	6mm	30 mm

MATERIALI - MATERIALS

TUBO HOSE		Treccia in acciaio Inox AISI 304. Tubo interno: gomma EPDM. Stainless steel Inox AISI 304 braid. Internal pipe: EPDM rubber.
RACCORDI FITTINGS		Ottone CW617N Brass CW617N
BUSSOLE SLEEVES		Acciaio INOX AISI 304 Stainless steel AISI 304

DN 8



Flessibile in Acciaio Inox AISI 304 - DN8 M12x1 - 3/8" F.
Stainless Steel Flexible hose AISI 304 - DN8 M12x1 - 3/8" F.

[illegible]

Flessibile in Acciaio Inox AISI 304 - DN8 M12x1 - 1/2" F.
Stainless Steel Flexible hose AISI 304 - DN8 M12x1 - 1/2" F.

[illegible]