Codice Dianflex: 353-42055

DOSAMAK 360°

Dosatore di polifosfato a polvere

Powdered polyphosphate dispenser



CARATTERISTICHE	
Dosaggio	3ppm (3mg/L)
Pres. max esercizio	5 bar
Temp. °C	1°-45°

Descrizione

I dosatori di polifosfati serie “DOSAMAK 360°” sono stati progettati per essere installati sulle tubature che portano l’acqua nella caldaia per ridurre la presenza di calcare rendendosi molto utili in impianti con acqua dura. Questo filtro/ dosatore trova una facile applicazione su caldaie e scaldabagni, prevendo la possibilità di incrostazioni di calcare, il dosatore è disponibile con valvola bypass, per consentire una facile sostituzione della ricarica una volta esaurita. Grazie alla testa regolabile è possibile installare il dosatore anche negli spazi più ridotti.

Viene fornito completo di:

- Ricarica in stick pronto uso.
- Chiave per smontaggio della ghiera.
- Guarnizioni.

Materiale costruzione:

- Testata: PP
- Attacchi: ottone
- Guarnizioni: nbr
- Bicchiere: san trasparente atossico

Description

The “DOSAMAK 360°” scale inhibitor feeders series has been designed to be installed on the pipes that bring water into the boiler and prevent scale, making them very useful in presence of hard water. This feeder finds
an easy application on boilers and water heaters, preventing the possibility of scale encrustations. feeder finds is available also with bypass valve, to allow easy replacement of the cartridge once exhausted. Thanks
to the adjustable head feeder finds can also be installed in the smallest spaces.

It’s provided complete of:

- Ready-to-use stick refill
- Key for disassembling the ring nut.
- Seals.

Construction materials:

- Head: PP
- Connections: brass
- Gaskets: nbr
- Bowl: san

Codice Code	Descrizione Description	AxBxC (mm)	Portata Flow rate	Imballo master carton			
				Pz. | Pcs	Kg.	AxBxC (cm)	
MKDPTP360	**DOSAMAK 360** Dos. prop. polifosfati att. 1/2” 360° con bypass. Scale inhibitor feeder 360°- 1/2” connections with bypass – con ghiera	170x65x140	1300 l/h	12	7,8	40x37x24	